

Aerial Drop Wire

ADW



SPECIFICATIONS

Conductor	Solid annealed copper
Insulation	Individual conductors insulated with solid polyolefin in distinctive colors; 2-pair color code is Blue/White and Orange/Red and 4-pair color code is Blue/White, Orange/Red, Black/Green and Yellow/Brown
Core Assembly	Individual conductors twisted into pairs
Strength Members	Fiberglass strength members placed in the jacket parallel to the core assembly
Rip cord	Placed parallel to the core
Jacket	Sky blue grey weather-resistant PVC jacket extruded over the strength members and bonded to the fiberglass strength members
Standards Compliance	RoHS-compliant

PRODUCT DESCRIPTION

ADW is a PVC jacketed 2-pair or 4-pair aerial service wire designed for use in extending telephone service to subscriber premises from the distribution cable or cable terminal. Major features include small size and light weight coupled with abrasion resistant jacket. Standard hardware and installations procedures are directly applicable to this product.

FEATURES

- Twisted pairs with varying lays
- Fiberglass strength members
- Rip cord
- Weather-resistant PVC jacket extruded over the strength members and bonded to the fiberglass strength members

BENEFITS

- Minimizes resistance unbalance
- Provides the necessary longitudinal strength
- Facilitates jacket removal
- Protects the core from mechanical damage, degradation by sunlight and the ingress of moisture
- Provides the required strength characteristics

ELECTRICAL SPECIFICATIONS

Conductor Size AWG (mm)	Average Mutual Capacitance @ 1,000 Hz nF/mile (nF/km)	Insulation Resistance @ 60°F (16°C) megohm-mile (megohm-km)	Capacitance Unbalance @ 1 kHz Pair to Pair Maximum pF @ 1 kft (pF @ 1 km)	Conductor DC Resistance @ 20°F (-7°C) Maximum Individual Ohms/kft (Ohms/km)	Resistance Unbalance Maximum Individual Pair %	Dielectric Strength DC Potential - Volts Minimum Conductor to Conductor
22 (0.64)	113 (70)	380 (610)	80 (145)	16.8 (55)	5.0	4,000

PART NUMBERS AND PHYSICAL CHARACTERISTICS

Part Number	Pair Count	AWG (mm)	Nominal Diameter in (mm)	Approx. Weight lbs/kft (kg/km)	Standard Length ft (m)	Package
12-022-09	2	22 (0.64)	0.26 (6.6)	30 (45)	1,476 (450)	Coil
12-021-09	2	22 (0.64)	0.26 (6.6)	30 (45)	656 (200)	POP™ Box
12-041-09	4	22 (0.64)	0.33 (8.4)	55 (80)	820 (250)	Coil
12-043-09	4	22 (0.64)	0.33 (8.4)	55 (80)	328 (100)	POP Box



TECHNICAL GUIDELINE

Sag and Tension Technical Guidelines are available for these products. Refer to the "Resources" section on our site for more information.